

What is claimed is:

Sub
ai

1. A plasma display panel comprising:

scan electrodes for selecting a row of a matrix

5 display;

data electrodes for selecting a column;

a partition for defining a discharge space at least
for each column;

10 k ($k \geq 2$) of the data electrodes being arranged for
each column of the matrix display, the data electrode
being continuous from one end of the column to the other
end;

15 all the scan electrodes within a display screen
being classified into k groups, one of the k groups being
assigned to k data electrodes in each column; and

each of the data electrodes being crossed with or
opposed to scan electrodes belonging to the group that is
assigned to the data electrode without overlapping a
partition and is crossed with other scan electrodes with
20 overlapping the partition.

2. The plasma display panel according to claim 1,
wherein k of the scan electrodes, each of which is
selected from each of the k groups within the display
screen, are connected electrically.

25 3. The plasma display panel according to claim 1,
wherein both ends of all data electrodes are led out of a
sealing member that surrounds the display screen so as to
close the discharge space.

30 4. The plasma display panel according to claim 1,
wherein each of the data electrodes is widened locally in

103410 2204860

a plan view at portions being crossed with or opposed to scan electrodes belonging to the group that is assigned to the data electrode.

5 5. A method of driving a plasma display panel
having scan electrodes for selecting a row of a matrix display, data electrodes for selecting a column, and a partition for defining a discharge space at least for each column, the method comprising the steps of:

10 arranging k ($k \geq 2$) data electrodes for each column of the matrix display, the data electrode being continuous from the first end to the second end in the column direction;

15 classifying all the scan electrodes within a display screen into k groups, and assigning one of the k groups to k data electrodes in each column;

20 setting each data electrode to cross or oppose scan electrodes belonging to the group that is assigned to the data electrode without overlapping a partition and to cross or oppose other scan electrodes with overlapping the partition;

connecting electrically k of the scan electrodes each of which is selected from each of the k groups within the display screen; and

25 selecting simultaneously k rows corresponding to the scan electrodes connected electrically when potentials of the scan electrodes and data electrodes are controlled in accordance with display contents for addressing.

30 6. The method according to claim 5, wherein the selecting step includes the step of selecting k rows from one end of the row arrangement to the other end, and

5

for row selection of a matrix display;

10

15